



X STANDALONE AXIS
ASME-TLMG00100303QBS0650
CHARON2 X with AccurET Modular

Data sheet

Version 1.1

ETEL

AXIS DESIGNATION		
Number of controlled axes		1
Axes name		X
Thrust transmitter: DD (direct drive) or ID (indirect drive)		DD

TESTING CONDITIONS	UNIT	
Position controller	-	Modular 300 7/15 Arms
Motion controller	-	UltimET
Rated payload	kg	5
Rated input voltage	VDC	96
Tool point position	mm	195
Ambient temperature	°C	22 ±1
Isolation system	-	QuiET

DIMENSIONAL DATA	UNIT	
Width	mm	336
Length	mm	1050 with handles / 984 without handles
Height	mm	144
Total stroke	mm	650
Moving mass (without payload)	kg	6
Total mass (without payload)	kg	53

FORCE CAPABILITIES (1)	UNIT	
Peak force	N	332
Continuous force	N	130
Standstill force	N	98
Max. detent force(average to peak)	N	7.1
Static friction (maximal value)	N	22
Dynamic friction (maximal value)	N/(m/s)	22

LOAD CAPACITIES	UNIT	
Maximum payload	kg	35

DYNAMIC PERFORMANCE	UNIT	
Duty cycle	%	30
Maximum speed	m/s	1
Maximum acceleration	m/s ²	20
Typical position stability at 2kHz	nm	±10

ACCURACY	UNIT	
Positioning accuracy (without mapping)	µm	±12.5
Positioning accuracy (with mapping)	µm	±1
Bidirectional repeatability	µm	±0.3
Horizontal straightness / radial runout	µm	±2.5
Vertical straightness / total axial error at tool point	µm	±2
Roll	arcsec	±3
Pitch	arcsec	±3.5
Yaw	arcsec	±5

WORKING ENVIRONMENT	
Clean room compatibility (2)	ISO 2

ELECTRICAL SPECIFICATIONS (1)		UNIT	
	Motor type	-	Ironcore
	Motor model	-	LMG10-030-3QB-219
	Number of phases	-	3
Kt	Force constant	N/Arms	26.6
Ku	Back EMF constant (3)	Vrms/(m/s)	16.2
Km	Motor constant	Nm/√W	16.8
R20	Electrical resistance at 20 °C (3)	Ohm	1.68
L1	Electrical inductance (3)	mH	9.02
Ip	Peak current	Arms	15
Ic	Continuous current	Arms	5
Is	Standstill current	Arms	3.79
ns	Standstill speed	mm/s	0.22
Um	Max. input voltage	VDC	100
Pc	Max. cont. power dissipation	W	77.6
2tp	Magnetic period	mm	32

ENCODER CHARACTERISTICS		UNIT	
	Encoder and signal type	-	Optical - incremental
	Output signal	-	1 Vpp
	Signal period or line count	µm	4
	Reference mark	-	One
	Power supply	V	5

TYPICAL MOVE AND SETTLE TIMES		UNIT	
	Move 1: 10 µm within ±100 nm window	ms	40
	Move 2: 25 mm within ±100 nm window	ms	130
	Move 3: 80 mm within ±100 nm window	ms	185

GUIDING ELEMENTS		
Type		Ball bearing

MATERIAL AND FINISH		
Baseplate		Granite
Carriage		Stainless steel

According to the Machinery Directive 2006/42/EC, the system presently described falls into the "partly completed machinery" category and fully complies with it as long as the system is operated according to the working conditions described in the corresponding manual. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the system is used in an improper way.

Notes: The specifications given may be mutually exclusive. Unless stated otherwise, all measurements are made within the testing conditions.

(1) Tolerances on electrical parameters are available on request.

(2) Under laminar flow conditions at 0.25 m/s along X axis. Measured at 230 mm from the bottom surface of the stage. Contact ETEL for more details.

(3) Terminal to terminal.