



XYZ3™ STACKED SYSTEM

ASME-NNNN-06-0475-0410xx

CHARON2 XYZ3™ with AccurET VHP

Data sheet

Version 2.0

ETEL

AXIS DESIGNATION

Number of controlled axes	6				
Axes name	X (bottom axis)	Y (top axis)	Fine Z	Tip-Tilt	Theta
Thrust transmitter: DD (direct drive) or ID (indirect drive)	DD	DD	DD	DD	DD

TESTING CONDITIONS

	UNIT					
Position controller	-	VHP 100 10/30 Arms		VHP 48 5/10 Arms		VHP 100 7/15 Arms
Motion controller	-	UltimET				
Rated payload (1)	kg	2				
Rated inertia (1)	kg.m ²	-	-	-	-	0.018
Rated input voltage	VDC	96	96	48		96
Tool point position	mm	275 above bottom surface				
Ambient temperature	°C	22 ±1				
Isolation system	-	QuiET				

DIMENSIONAL DATA

	UNIT					
Width	mm	824				
Length	mm	953				
Height	mm	230				
Total stroke	mm or °	475	410	±2	±0.08	Infinite
Moving mass (without payload)	kg	25.8	13.2	4.2	-	-
Total mass (without payload)	kg	58				
Rotor inertia (without payload)	kg.m ²	-	-	-	-	0.004

FORCE / TORQUE CAPABILITIES (2)

	UNIT					
Peak force / torque	N or Nm	512	298	65.3	-	7.87
Continuous force / torque	N or Nm	130	54.3	15.7	-	1.74
Standstill force / torque	N or Nm	98	40.9	-	-	1.32
Max. detent force / torque (average to peak)	N or Nm	7.1	7.9	-	-	0
Static friction (maximal value)	N or Nm	22	22	-	-	1
Dynamic friction (maximal value)	N/(m/s) or Nm/(rad/s)	22	22	-	-	0.03

LOAD CAPACITIES

	UNIT					
Maximum axial load	N	-	-	-	-	30
Maximum payload	kg	2				

DYNAMIC PERFORMANCE

	UNIT					
Duty cycle	%	20	20	-	-	10
Maximum speed	m/s or rad/s	1	1	0.1	-	30
Maximum acceleration	m/s ² or rad/s ²	10	10	3	-	180
Typical position stability at 2kHz	nm or arcsec	±2	±2	±3	-	±0.02

ACCURACY

	UNIT					
Positioning accuracy (without mapping)	µm or arcsec	±20		-	-	-
Positioning accuracy (with mapping)	µm or arcsec	±1		-	-	-
Bidirectional repeatability	µm or arcsec	±0.4		±0.03	-	±2
Horizontal straightness / radial runout	µm	±3	±3.5	-	-	±3.5
Vertical straightness / total axial error at tool point	µm	±2.5	±5	-	-	±3
XY displacement while moving in Z	µm	-		±0.1	-	-
Orthogonality	arcsec	±15		-	-	-
Roll	arcsec	±5	±10	-	-	-
Pitch	arcsec	±5	±15	-	-	-
Yaw	arcsec	±10	±10	-	-	-

WORKING ENVIRONMENT

Clean room compatibility (3)	ISO 2
------------------------------	-------

ELECTRICAL SPECIFICATIONS (2)		UNIT	X (bottom axis)	Y (top axis)	Fine Z	Tip-Tilt	Theta
	Motor type	-	Ironcore	Ironcore	Electro-magnet		Toothless
	Motor model	-	LMG10-030-3QB-H01	LMG-05-030-3RA-H01	EMF-14.5-058-1NA-219		TTB0126-030-3NA
	Number of phases	-	3	3	3x single phase		3
Kt	Force constant	N/Arms or Nm/Arms or N/A _{DC}	26.6	24.6	19.6		1.23
Ku	Back EMF constant (4)	V _{rms} /(m/s) or V _{rms} /(rad/s) or V _{DC} /(m/s)	16.2	14.9	19.6		0.71
Km	Motor constant	Nm/√W	16.8	13.2	8.34		-
R20	Electrical resistance at 20 °C (4)	Ohm	1.68	2.31	5.50		10.50
L1	Electrical inductance (4)	mH	9.02	10.8	13.50		2.65
I_p	Peak current	Arms or A _{DC}	30.0	19.9	3.38		6.90
I_c	Continuous current	Arms or A _{DC}	5.00	2.26	0.80		1.47
I_s	Standstill current	Arms or A _{DC}	3.79	1.71	-		1.11
n_s	Standstill speed	mm/s or rad/s	0.22	0.2	-		0.0016
U_m	Max. input voltage	VDC	100	100	48		100
P_c	Max. cont. power dissipation	W	77.6	20.4	3.88		41.9
2τ_p	Magnetic period	mm	32	32	-		-
2p	Number of poles	-	-	-	-		28

ENCODER CHARACTERISTICS		UNIT				
	Encoder and signal type	-	Optical Incremental	Optical Incremental	Optical Incremental	Optical Incremental
	Output signal	-	1 Vpp	1 Vpp	1 Vpp	1 Vpp
	Signal period or line count	µm or period/turn	4	4	4	18000
	Reference mark	-	One	One	One centered in Z	One
	Power supply	V	5	5	5	5

TYPICAL MOVE AND SETTLE TIMES		UNIT				
	Move 1: 10 µm within ±100 nm window	ms	50	-	-	-
	Move 2: 25 mm within ±100 nm window	ms	170	-	-	-
	Move 3: 80 mm within ±100 nm window	ms	250	-	-	-
	Move 4: 100 µm within ±30 nm window	ms	-	-	60	-
	Move 5: 1 mm within ±30 nm window	ms	-	-	100	-
	Move 6: 90 deg within ±40 µdeg	ms	-	-	-	360
	Move 7: 180 deg within ±40 µdeg	ms	-	-	-	525
	Move 8: 360 deg within ±40 µdeg	ms	-	-	-	850

GUIDING ELEMENTS						
	Type	-	Ball bearing	Ball bearing	Flexures	Crossed roller bearing

MATERIAL AND FINISH						
	Baseplate	-	Granite	Aluminium & Silicon Alloy	Anodized aluminium	-
	Carriage	-	Aluminium & Silicon Alloy	Stainless steel	Anodized aluminium	Stainless steel

According to the Machinery Directive 2006/42/EC, the system presently described falls into the "partly completed machinery" category and fully complies with it as long as the system is operated according to the working conditions described in the corresponding manual. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the system is used in an improper way.

Notes: The specifications given may be mutually exclusive. Unless stated otherwise, all measurements are made within the testing conditions.

- (1) Payload can be assimilated to a cylinder of diameter 270 mm, 19 mm thick, weighting 2 kg. Inertia is expressed with respect to the center of gravity of the payload, Z being the axis of rotation.
- (2) Tolerances on electrical parameters are available on request.
- (3) Under laminar flow conditions at 0.25 m/s along Y axis. Measured at 230 mm from the bottom surface of the stage. Contact ETEL for more details.
- (4) Terminal to terminal.