

TORQUE MOTOR

TMM0210-070

PERFORMANCE		Winding codes	3TAN	3TBS
		UNIT	FREE AIR CONVECTION (with glued stator)	FREE AIR CONVECTION (with glued stator)
Tp	Peak torque	Nm	309	309
Tc	Continuous torque	Nm	66.4	66.4
Ts	Stall torque	Nm	50.4	50.4
Kt	Torque constant	Nm/Arms	15.6	7.78
Ku	Back EMF constant (*)	Vrms/(rad/s)	9.00	4.50
Km	Motor constant	Nm/√W	4.44	4.44
R20	Electrical resistance at 20°C (*)	Ohm	8.19	2.05
L1	Electrical inductance (*)	mH	41.9	10.5
Ip	Peak current	Arms	28.1	56.2
Ic	Continuous current	Arms	4.33	8.67
Is	Stall current	Arms	3.28	6.57
Pc	Max. continuous power dissipation	W	320	320

SPECIFICATIONS		UNIT		
Udc	Nominal input voltage	VDC	600	600
τth	Thermal time constant	s	1450	1450
Rth	Thermal resistance	K/W	0.307	0.307
2p	Number of poles	-	44	44
J	Rotor inertia	kg.m ²	0.0207	0.0207
Mr	Rotor mass	kg	3.48	3.48
Ms	Stator mass	kg	6.49	6.49
Td	Max. detent torque (average to peak)	Nm	1.5	1.5
ns	Stall speed	rpm	0.019	0.019

Notes: (*) terminal to terminal. Ambient temperature = 20 °C. Max. coil temperature = 130 °C.
 Hypothesis and tolerances are in ETEL's Handbook. Stator connected to a total surface of 0.14 m² and rotor to a total surface of 0.074 m²

Caution: Any use of the motor beyond speed/force limit could lead to hazardous voltage and serious injuries. Customer is responsible for setting safeties/limitations that will keep the motor in its safe operating area. ETEL cannot be held responsible if the motor is used in an improper way.

